

Miscellaneous

Bunsen burner, with flame stabilizer and air regulation, made of nickel-plated brass

Type	Measurement	Order number Natural gas 23 mbar	Order number Propane / Butane 80 mbar	Order number Allgas 5-100 mbar
	Ø11 x 130 mm	7 401 000	7 401 010	-
with stopcock	Ø11 x 130 mm	7 401 001	7 401 011	-
	Ø13 x 150 mm	7 401 002	7 401 012	-
with stopcock & pilot flame	Ø13 x 160 mm	7 401 003	7 401 013	-
with stopcock	Ø11 x 130 mm	-	-	7 401 024
with stopcock, pilot flame and tilt stopcock	Ø13 x 175 mm	-	-	7 401 025



Meker burner, with air regulation, grid and stopcock, made of nickel-plated brass

Type	Measurement	Order number Natural gas 23 mbar	Order number Propane / Butane 80 mbar	Order number Allgas 5-100 mbar
grid head	Ø15 x 140 mm	7 401 030	7 401 040	7 401 050
grid head	Ø20 x 155 mm	7 401 031	7 401 041	7 401 051
grid head	Ø25 x 170 mm	7 401 032	7 401 042	7 401 052
grid head	Ø30 x 200 mm	7 401 033	7 401 043	7 401 053
perforated head	Ø20 x 155 mm	-	-	7 401 060
perforated head	Ø25 x 180 mm	-	-	7 401 061
perforated head	Ø30 x 185 mm	-	-	7 401 062



Safety burner, with needle valve, air regulation and pilot flame, made of nickel-plated brass

	Order number Natural gas 23 mbar	Order number Propane / Butane 80 mbar	Order number Allgas 5-100 mbar
	7 401 070	-	7 401 072



Safety burner, instant safety flame push button ignition. Used in microbiology, bacteriology and for general use for fast heat and fusion. Powered by a 1.5V battery

	Order number Natural gas 23 mbar	Order number Propane / Butane 80 mbar	Order number Allgas 5-100 mbar
	-	7 401 080	-



Digital gas burner

with LCD display, multi-lingual, joystick navigation, duration display, manual mode / floor switch

Type	Order number
Schuett Phoenix II standard controlled burning duration 1sec up to 120min, firing time display, automatic stop when not in use, overheat protection, exact economic flame adjustment, stable flame even at intense airflow, flame and ignition monitoring, angle adjustment 128 x 160 x h85mm, 100-240V, 50/60Hz, ~1kg	7 401 200
safety gas tubing for allgas	0.75m: 7 401 215
safety gas tubing for Propane / Butane, with thread connections	0.5m: 7 401 216 2.0m: 7 401 217
safety gas tubing for allgas with standard connection 1/2" for gas outlet (TAE)	1.0m: 7 401 218 2.0m: 7 401 219
adapter with pressure reducing valve for CV 360 butane cartridges	7 401 211
adapter with pressure reducing valve for C 206 butane cartridges and safety gas tubing 0.5m	7 401 212
glass splatter guard	7 401 213
flame shield, stainless steel	7 401 214

