

## Class AS

- color-code to avoid confusion
- made of soda-lime glass
- zero point at the upper end of the scale
- main point ring graduation
- tolerance according to DIN EN ISO 835
- DE-M marked according to the German calibration law
- calibrated to deliver (EX), 5 sec waiting time
- standard and special sizes available
- inclusive batch certificate




Capacity ml	Division ml	Tolerance ml	Color-Code	Delivery time seconds	Order number	
					brown graduated	blue graduated
0.1	0.01	±0.006	white	2 - 8	3 510 011	3 510 011 BL
0.2	0.01	±0.006	black	2 - 8	3 510 021	3 510 021 BL
0.2*	0.002	±0.006	white x2	2 - 8	3 510 022	3 510 022 BL
0.5	0.01	±0.006	yellow x2	4 - 10	3 510 051	3 510 051 BL
1	0.01	±0.007	yellow	4 - 10	3 510 101	3 510 101 BL
1	0.1	±0.007	red	4 - 10	3 510 110	3 510 110 BL
2*	0.01	±0.010	white x2	4 - 10	3 510 201	3 510 201 BL
2	0.02	±0.010	black	4 - 10	3 510 202	3 510 202 BL
2	0.1	±0.010	green	4 - 10	3 510 210	3 510 210 BL
5	0.05	±0.030	red	7 - 13	3 510 505	3 510 505 BL
5	0.1	±0.030	blue	7 - 13	3 510 510	3 510 510 BL
10	0.1	±0.050	orange	7 - 13	3 510 710	3 510 710 BL
20	0.1	±0.100	yellow x2	11 - 17	3 510 810	3 510 810 BL
25	0.1	±0.100	white	11 - 17	3 510 910	3 510 910 BL
50*	0.2	±0.200	black	-	3 510 950	3 510 950 BL

\* special size in addition to the ISO 835 range, without conformity certificate

## Class B

- color-coded to avoid confusion
- made of soda-lime glass
- zero point at the upper end of the scale
- short line graduation
- tolerance according to DIN EN ISO 835
- our error ranges are better than the DIN EN ISO 835 requirements
- calibrated to deliver (EX)
- without waiting time
- standard and special sizes available



Capacity ml	Division ml	Tolerance		Color-Code	Delivery time seconds	Order number	
		witeg ml	ISO ml			white graduated	brown graduated
0.1	0.01	±0.010	±0.010	white	2 - 12	3 500 011 W	3 500 011
0.2	0.01	±0.010	±0.010	black	2 - 12	3 500 021 W	3 500 021
0.2*	0.002	±0.010	±0.010	white x2	2 - 12	3 500 022 W	3 500 022
0.5	0.01	±0.010	±0.010	yellow x2	2 - 12	3 500 051 W	3 500 051
1	0.01	±0.010	±0.010	yellow	2 - 12	3 500 101 W	3 500 101
1	0.1	±0.010	±0.010	red	2 - 12	3 500 110 W	3 500 110
2*	0.01	±0.015	±0.020	white x2	2 - 12	3 500 201 W	3 500 201
2	0.02	±0.015	±0.020	black	2 - 12	3 500 202 W	3 500 202
2	0.1	±0.015	±0.020	green	2 - 12	3 500 210 W	3 500 210
5	0.05	±0.040	±0.050	red	5 - 15	3 500 505 W	3 500 505
5	0.1	±0.040	±0.050	blue	5 - 15	3 500 510 W	3 500 510
10	0.1	±0.080	±0.100	orange	5 - 15	3 500 710 W	3 500 710
20	0.1	±0.150	±0.200	yellow x2	9 - 20	3 500 810 W	3 500 810
25	0.1	±0.200	±0.200	white	9 - 20	3 500 910 W	3 500 910
50*	0.2	±0.400	±0.400	black	-	3 500 950 W	3 500 950

\* special size in addition to the ISO 835 range