

Hotplate

analog, up to 380°C, ceramic-coated plate

HP-A analog, 70°C - 380°C

Ideal for:

- sample drying and general lab heating applications

Features:


- up to 380°C
- ceramic-coated aluminium plate 180x180 / 260x260 mm
- heat-, chemical- and restricted acid-resistant
- powder-coated body
- CE certified and unique serial number for tracing

Safety mechanism:

- operation LEDs

Controller:

- **PWM controller**



HP-20A



HP-30A

Model	HP-20A	HP-30A
Body	powder-coated aluminium	powder-coated steel
Plate	ceramic-coated aluminium 180x180 mm	ceramic-coated aluminium 260x260 mm
Temperature range & accuracy	70°C - 380°C, ±0.3°C	
Temperature resolution	0.5°C control	
Temperature uniformity	specially designed heating module: temperature difference less than 10%	
Heating power / consumption	600W	1.2kW
Controller	superior linearity PWM Controller	
Permissible temperature & RH %	ambient temperature +5 ~ 50°C, 85% RH	
Dimension & weight	206x307xh99 mm, 2.8 kg	286x387xh99 mm, 3.2 kg
Packaging size	400x280xh200 mm, 5 kg	430x320xh200 mm, 5 kg
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz	
Order number 230V	DH.WHP03120	DH.WHP03121
Order number 120V	DH.WHP02120	DH.WHP02121

Accessories:



Stand rod RD200 Ø12xL450 mm with stainless steel thread

DH.WHP503036

Holder, clamp and clip

DH.WHP503012