

Vacuum pump (oil-free)

ROCKER
make filtration easy

Rocker 300 / 300 DC up to -680 mmHg, 25 l/min, 50dB



Rocker 300



Rocker 300 DC

Ideal for:

- filtration for microbiology test
- air sampling
- suspended solid test
- vacuum filtration

Features:

- lubricant and oil free piston
- no air pollution
- maintenance-free
- Prote™ filter prevents liquid from being sucked into the pump and filters particles as well as moisture
- CE certified

Safety mechanism:

- thermal protection device ensures shutting down the pump when overheated and resumes working when the temperature cooled down

Model	Rocker 300		Rocker 300 DC
Max. power (W)	65	60	35
Max. current (A)	0.7	0.3	3
Max. vacuum	-680 mmHg		-650 mmHg
Max. flow rate	23 l/min	20 l/min	25 l/min
Moisture trap / vacuum regulator	Yes		Yes
Overflow protection	Yes		Yes
Motor rotation	1750 rpm	1450 rpm	1800 rpm
Horse power	1/8 HP		1/8 HP
Noise level	50 dB		50 dB
Port thread	5/16 inch (8 mm)		5/16 inch (8 mm)
Net weight	4.1 kg		3.5 kg
Dimension (LxWxH)	26.8 x 13.5 x 20.4 cm		26.8 x 13.5 x 20.4 cm
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz		
Order number 110V	00829 167300-11	-	-
Order number 230V	-	00829 167300-22	-
Order number DC 12V	-	-	00829 167330-00