

Vacuum pump (oil-free)

ROCKER
make filtration easy

Rocker 400 / 410 up to -735 mmHg, 37 l/min, 52dB



Rocker 400



Rocker 410

Ideal for:

- filtration for microbiology test
- air sampling
- suspended solid test
- vacuum filtration

Features:

- lubricant and oil free piston
- no air pollution
- maintenance-free
- Prote™ filter prevents liquid from being sucked into the pump and filters particles as well as moisture
- CE certified

Safety mechanism:

- thermal protection device ensures shutting down the pump when overheated and resumes working when the temperature cooled down

Model	Rocker 400		Rocker 410	
Max. power (W)	100	80	100	80
Max. current (A)	1.0	0.4	1.0	0.4
Max. vacuum	-680 mmHg		-735 mmHg	
Max. flow rate	37 l/min	34 l/min	23 l/min	20 l/min
Moisture trap / vacuum regulator	Yes		Yes	
Overflow protection	Yes		Yes	
Motor ration	1750 rpm	1450 rpm	1750 rpm	1450 rpm
Horse power	1/6 HP		1/6 HP	
Noise level	52 dB		52 dB	
Port thread	5/16 inch (8 mm)		5/16 inch (8 mm)	
Net weight	5.2 kg		5.2 kg	
Dimension (LxWxH)	31.0 x 13.5 x 20.4 cm		31.0 x 13.5 x 20.4 cm	
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz			
Order number 110V	00829 167400-11	-	00829 167410-11	-
Order number 230V	-	00829 167400-22	-	00829 167410-22