

## Volumetric flask with socket amber-stained, class A



- made of borosilicate glass 3.3
- tolerance according to DIN EN ISO 1042
- DE-M marked according to the German calibration law
- standard and special sizes available
- inclusive batch certificate

Capacity	Tolerance	Socket	Order number	
ml	ml	ST	white graduated with ST-hollow glass stopper	white graduated with PE-stopper
2	±0.040	10/19	3 670 022	3 670 022 P
5	±0.025	7/16	3 670 000	3 670 000 P
5	±0.040	10/19	3 670 015	3 670 015 P
10	±0.025	7/16	3 670 001	3 670 001 P
10	±0.040	10/19	3 670 012	3 670 012 P
10*	±0.060	14/23	3 670 00114	3 670 00114 P
15*	±0.040	10/19	3 670 016	3 670 016 P
15*	±0.060	12/21	3 670 0016	3 670 0016 P
20*	±0.040	7/16	3 670 013 7	3 670 013 7 P
20	±0.040	10/19	3 670 002	3 670 002 P
20	±0.060	12/21	3 670 013	3 670 013 P
20*	±0.060	14/23	3 670 017	3 670 017 P
25	±0.040	10/19	3 670 003	3 670 003 P
25	±0.060	12/21	3 670 014	3 670 014 P
25*	±0.060	14/23	3 670 018	3 670 018 P
50	±0.060	12/21	3 670 005	3 670 005 P
50	±0.100	14/23	3 670 006	3 670 006 P
100	±0.100	12/21	3 670 010	3 670 010 P
100	±0.100	14/23	3 670 011	3 670 011 P
125*	±0.100	14/23	3 670 125	3 670 125 P
150*	±0.100	14/23	3 670 150	3 670 150 P
200	±0.150	14/23	3 670 020	3 670 020 P
250	±0.150	14/23	3 670 025	3 670 025 P
250*	±0.400	29/32	3 670 025 29	3 670 025 29 P
300*	±0.150	14/23	3 670 030	3 670 030 P
500*	±0.250	14/23	3 670 049	3 670 049 P
500	±0.250	19/26	3 670 050	3 670 050 P
500*	±0.400	29/32	3 670 051	3 670 051 P
1000	±0.400	24/29	3 670 100	3 670 100 P
1000	±0.600	29/32	3 670 101	3 670 101 P
2000	±0.600	29/32	3 670 200	3 670 200 P
5000	±1.200	34/35	3 670 500	3 670 500 P

\* special size in addition to the ISO 1042 range, with conformity certificate



## Volumetric flask with screw cap, class A



- made from Duran® tubing
- DE-M marked according to the German calibration law
- tolerance according to DIN EN ISO 1042
- inclusive batch certificate

Capacity	Tolerance	Screw thread	Order number	
ml	ml	GL	brown graduated with screw cap	
5	±0,040	14	3 642 000	
10	±0,040	14	3 642 001	
20	±0,040	14	3 642 002	
25	±0,040	14	3 642 003	
50	±0,060	18	3 642 005	
100	±0,100	18	3 642 010	
200	±0,150	18	3 642 020	
250	±0,150	18	3 642 025	
500	±0,250	25	3 642 050	
1000	±0,400	32	3 642 100	
2000	±0,600	32	3 642 200	
5000	±1,200	32	3 642 500	

